

Table 36. Presentation of complied features from type 8 dwelling/byre houses. Measurements in metres (m). Estimated measurements in italics.

House number	House number	Type	Orientation	Length of post-setting	Total length	Max width	Floor area m ²	Trestle width	Max. Trestle width	Trestle width	Corner posts	Corner posts	TQ	Wall post distances		Longwall curvature	Shape of short wall	Distance: gable to pair I (west)	Distance: gable to pair N (east)	Distances between trestles											West				East				Roof-bearing postholes								Door postholes				LENGTH interpretation			I4C-date	I SD. (Iσ)	Calibrated age	T-number	Comments
														N	S					Door width		Door recess		Surface dimension		Depth		Living area	Byre	Living area	west	Byre	east	BP	BC-AD																							
								N	S	N	S	N								S	Min-max	Mean	Min-max	Mean	Number	Shape I:round 2:oval	Min-max									Mean	Min-max	Mean																				
								1-2	2-3	3-4	4-5	5-6		6-7	7-8					8-9	9-10	10-11	N	S	N	S	N	S	N	S	Number	Shape I:round 2:oval	Min-max	Mean	Min-max	Mean	Number	Shape I:round 2:oval	Min-max	Mean	Min-max	Mean	west	Byre	east	BP	BC-AD	T-number	Comments									
50	L	8	322	30.1	35.5	6.7	231	2.3	2.9	2.5			2.3	1.14					2.9	4.1	3.0	2.9	3.1	3.4	2.9	2.7	2.7	2.5		1.1		0.7		1.1			21	2	0.26x0.33-0.62x0.73	0.47x0.64	0.09-0.38	0.26	2	2	0.38x0.48-0.35x0.45	0.37x0.47	0.12-0.15	0.14	22.10	13.40		1800	70	120-330	T-8547			
10A	XA	8	296	22.9	28.7	7.2	195	2.5	3.3	2.9	5.3	0.0	2.2	0.61	0.58		3	2.6	3.2	3.6	2.5	3.9	3.5	3.1	3.4	2.9			1.2		0.6		1.1		0.7	16	2	0.45x0.55-0.60x0.90	0.50x0.69	0.15-0.40	0.27	4	2	0.42x0.52-0.54x0.60	0.46x0.56	0.25-0.43	0.36	12.60	16.10		1760	70	130-390	T-5903				
20	XX	8	297	22.5	29.0	7.2	197	3.0	3.3	2.4	0.0	3.7	2.2				3	0.0	3.2	3.4	3.0	3.7	2.6	3.0	3.0	3.8			1.1	1.4						16	2	0.41x0.50-0.55x0.77	0.49x0.63	0.07-0.22	0.15	4	2	0.41x0.54-0.41x0.63	0.42x0.58	0.25-0.34	0.29	15.80	13.20		1750	70	210-400	T-8248				
107	CVII	8	309	22.1	27.5	6.0	165	2.0	2.8	2.4			2.1						2.5	2.5	2.7	2.1	3.1	2.7	3.3	3.2			1.6			1.0			16	2	0.22x0.31-0.45x0.60	0.35x0.48	0.04-0.34	0.15	4	2	0.33x0.38-0.32x0.48	0.32x0.44	0.07-0.16	0.10	15.60	11.90		1770	70	130-380	T-8243	inverted orientation				
135	CXXXV	8	309	17.6	23.0	6.4	147	2.0	2.8		3.5		2.3				3	2.8		3.1	2.5	1.5	3.1	2.4	2.4	2.6			0.9			2.3			10	2	0.37x0.62-0.66x0.83	0.53x0.70	0.14-0.38	0.26	4	2	0.35x0.43-0.45x0.65	0.39x0.52	0.20-0.32	0.28	12.90	10.10		1730	65	240-400	T-8708	inverted orientation				
220	CCXX	8	311	18.3	36.0	7.5	260	2.9	3.6	3.4			2.1	1.2	1.2							3.4	3.5	3.1	2.4	2.9	2.4	0.0	0.0							2	2	0.45x0.50-0.45x0.80	0.47x0.70					16.00	20.00		1700	80	240-430	T-9510	inverted orientation							
26B	XXXVI B	8.0	300.0	21.6	22.6	6.2	140	2.3	2.5	1.4	4.3	3.8	2.5				3.0	0.4	0.6	2.2	3.4	2.7	2.5	3.0	3.6	2.3	1.9			1.1	1.2	0.7		1.4		0.7	14	2	0.32x0.37-0.47x0.60	0.39x0.51	0.18-0.43	0.4	2.0	2.0	0.35x0.52	0.02-0.32	0.3	12.7	9.9		1470.0	70	410-690	T-6392	inverted orientation			
Mean			306	22.2	28.9	6.7	190.7	2.4	3.0	2.5	4.4	3.8	2.2	1	0.9		3	2.7	3.2	3.0	3.0	3.0	2.9	3.0	3.0	3.0	2.6	2.7	2.5	1.1	1.2	1.2	0.7		1.4		0.7	95	2	0.45x0.61	0.24	20	2	0.39x0.52	0.25	15.40	13.50											
35A	XXXVA	8	298	25.8	30.2	6.8	200	3.0	3.2	2.2	4.5	4.4	2.1				3		2.2	5.6																2	2	0.43x0.50-0.35x0.45	0.39x0.40			4	2	0.35x0.50					1580	60	410-560	TUa-126	inverted					
35B	XXXV B	8	298	25.0	29.6	6.8	195	3.0	3.2	2.5	4.5	4.1	2.1				3		2.5	4.8																2	2	0.43x0.50-0.35x0.45	0.39x0.40			4	2	0.35x0.50														

location of hearth

location of entrance(s)